

TABELLA PREFORI PER FILETTAURE

FILETTATURA AMERICANA
UNC PASSO GROSSO

Maschiatura UNC	Ø interno max mm.	punta Ø mm.
4-40	2,385	2,35
5-40	2,697	2,65
6-32	2,896	2,85
8-32	3,531	3,5
10-24	3,962	3,9
10-24	4,597	4,5
1/4-20	5,268	5,1
5/16-18	6,734	6,6
3/8-16	8,164	8
7/16-14	9,550	9,4
1/2-13	11,013	10,8
9/16-12	12,456	12,2
5/8-11	13,868	13,5
3/4-10	16,833	16,5
7/8-9	19,748	19,5
1"-8	22,598	22,25
1 1/8-7	25,349	25
1 1/4-7	28,824	28
1 3/8-6	31,120	30,5
1 1/2-6	34,295	34
1 3/4-5	39,814	39,5
2-4 1/2	45,598	45

FILETTATURA AMERICANA
UNF PASSO FINE

Maschiatura UNF	Ø interno max mm.	punta Ø mm.
4-48	2,459	2,4
5-44	2,741	2,7
6-40	3,023	2,95
8-36	3,607	3,5
10-32	4,166	4,1
12-28	4,724	4,7
1/4-28	5,580	5,5
5/16-24	7,038	6,9
3/8-24	8,626	8,5
7/16-20	10,030	9,9
1/2-20	11,618	11,5
9/16-18	13,084	12,9
5/8-18	14,671	14,5
3/4-16	17,689	17,5
7/8-14	20,663	20,5
1-12	23,569	23,25
1 1/8-12	26,744	26,5
1 1/4-12	29,919	29,5
1 3/8-12	33,094	33
1 1/2-12	36,269	36

FILETTATURA
WITHWORTH

Maschiatura W	Ø interno max mm.	punta Ø mm.
3/32 X 48	1,910	1,85
1/8 X 40	2,590	2,55
5/32 X 32	3,211	3,2
3/16 X 24	3,744	3,7
7/32 X 24	4,538	4,5
1/4 X 20	5,224	5,1
5/16 X 18	6,661	6,5
3/8 X 16	8,052	7,9
7/16 X 14	9,379	9,2
1/2 X 12	10,610	10,5
9/16 X 12	12,176	12
5/8 X 11	13,598	13,5
3/4 X 10	16,538	16,5
7/8 X 9	19,411	19,25
1 X 8	22,185	22
1 1/8 X 7	24,879	24,75
1 1/4 X 7	28,054	28
1 3/8 X 6	30,555	30,5
1 1/2 X 6	33,730	33,5
1 5/8 X 5	35,921	35,5
1 3/4 X 5	39,096	39
1 7/8 X 4 1/2	41,648	41,5
2 X 4 1/2	44,823	44,5

FILETTATURA GAS
CILINDRICA

Maschiatura GAS	Ø interno max mm.	punta Ø mm.
1/8 X 28	8,848	8,8
1/4 X 19	11,890	11,8
3/8 X 19	15,395	15,25
1/2 X 14	19,172	19
5/8 X 14	21,128	21
3/4 X 14	24,658	24,5
7/8 X 14	28,418	28
1 X 11	30,931	30,5
1 1/4 X 11	39,592	39,5
1 1/2 X 11	45,485	45
1 3/4 X 11	51,428	51
2 X 11	57,296	57
2 1/4 X 11	63,392	63,30
2 3/8 X 11	67,080	67
2 1/2 X 11	72,866	72,8
2 3/4 X 11	79,216	79,1
3 X 11	85,566	85,5
3 1/4 X 11	91,662	91,5
3 1/2 X 11	98,012	98
3 3/4 X 11	104,362	104
4 X 11	110,712	110,5

MASCHI
A RULLARE

passo grosso MF	passo	Ø foratura
M3	0,5	2,8
M4	0,7	3,7
M5	0,8	6,65
M6	1	5,55
M7	1	6,55
M8	1,25	7,45
M10	1,5	9,35
M12	1,75	11,2
M14	2	13,1

FILETTO CORAZZATO
DIN 40 430

Pg.	filetto	Ø interno max mm.	Ø foratura
7	20	11,43	11,4
9	18	14,01	14
11	18	17,41	17,25
13,5	18	19,21	19
16	18	21,31	21,25
21	16	27,03	26,9
29	16	35,73	35,6
36	16	45,73	45,6
42	16	52,73	52,6
48	16	58,03	57,9

FILETTATURA GAS
CONICA RC (ex BSPT)

maschiatura GAS RC	punta Ø mm
1/8 X 28	8,30
1/4 X 19	11,10
3/8 X 19	14,50
1/2 X 14	18,20
3/4 X 14	23,50
1 X 11	29,75
1 1/4 X 11	38,20
1 1/2 X 11	44
2 X 11	55,70

FILETTATURA CONICA
NPT

maschiatura NPT	punta Ø mm
1/8 X 27	8,5
1/4 X 18	11
1/2 X 14	18
3/4 X 14	23
1 X 1 1/2	29
1 1/4 X 1 1/2	38
1 1/2 X 1 1/2	44
2 X 1 1/2	56